

# Conventional Weatherproof Beacon

## CWST-RR-W5



### Features

- ▶ Approved to EN54-23, C & W categories
- ▶ Advanced optics ensures superior light coverage at low current draw
- ▶ Synchronised flash exceeds EN54-23 standard
- ▶ Red light flash
- ▶ Soft start feature reduces power surges during system start-up
- ▶ IP65

### Description

CWST-RR-W5 features high output LEDs, advanced optics and an innovative lens design, providing outstanding Omni-directional light coverage at low current draw. Specifically designed for, and approved to meet EN54-23, the CWST-RR-W5 delivers outstanding quality, reliability and long operational life. Weatherproof base provides IP65 for external use applications.

### Specification

Ordering Codes	CWST-RR-W5
Case Colour	Red
Lens Colour	Clear
LED Colour	Red
Cable Terminal Size	0.5-2.5 mm <sup>2</sup>
Material	Lens: PC Body: PC-ABS
Weight (g)	171
Dimensions	Ø 100 mm x H 97 mm
Operating Temperature	-25 °C to 70 °C
Relative Humidity	93% ±3% non-condensing
Ingress Protection	IP65
Operating Voltage EN54-23	12 to 29 V dc
Average Current Consumption	26 mA @ 29 V dc

## Product Performance

	Wall mount W Class	Wall Mount W Class	Ceiling Mount C Class	Ceiling Mount C Class
LED Colour	White	Red	White	Red
EN54-23 Coverage Volume Code	W-2.4-9.0	W-2.4-6.2	C-3-9.5 C-6-9.5 C-9-9.5	C-3-9.4 C-6-8.6
Installation Height (X)	2.4 m	2.4 m	3 m 6 m 9 m	3 m 6 m
EN54-23 Coverage (Y)	Cube YY 9.0 m	Cube YY 6.2 m	Cylinder Ø 9.5 m	Cylinder Ø 9.5 m 8.6 m
EN54-23 Coverage Volume	194 m <sup>3</sup>	92 m <sup>3</sup>	213 m <sup>3</sup> 425 m <sup>3</sup> 638 m <sup>3</sup>	208 m <sup>3</sup> 348 m <sup>3</sup>
Flash Rate	0.5 Hz	0.5 Hz	0.5 Hz	0.5 Hz
Operating Voltage Range	12 to 29 V	12 to 29 V	12 to 29 V	12 to 29 V
Synchronisation	Automatically on power up, exceeds EN54-23 standard			

## The Range

Part No.	Body Colour	Flash (LED) Colour	Base Option	Lens Colour
CWST-RW-S5	Red	White	Low Profile	Clear
CWST-RW-W5	Red	White	IP65/Deep	Clear
CWST-RR-S5	Red	Red	Low Profile	Clear
CWST-RR-W5	Red	Red	IP65/Deep	Clear
CWST-WW-S5	White	White	Low Profile	Clear
CWST-WW-W5	White	White	IP65/Deep	Clear
CWST-WR-S5	White	Red	Low Profile	Clear
CWST-WR-W5	White	Red	IP65/Deep	Clear

Hochiki Europe (UK) Ltd. reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki Europe (UK) Ltd. to be a complete and up-to-date description.