


# MARINE HCP-WM(SCI)

## Weatherproof Analogue Manual Call Point with SCI



### Features

- ▶ Fast response
- ▶ Integral short-circuit isolator
- ▶ Bi-coloured status LED
- ▶ Non-frangible element fitted as standard (conforms to EN54)
- ▶ Addressed with TCH-B100 Hand Held Programmer
- ▶ Surface mounted
- ▶ IP67 rated
- ▶ LPCB approved to EN54
- ▶ SIL Level 2 approved variants available

### Description

Model HCP-WM(SCI) is a weatherproof Manual Call Point with integral short-circuit isolator, which is fully compatible with Hochiki's ESP analogue addressable protocol. The unit incorporates a bi-coloured LED, which can be selected as pulsing/non-pulsing\*1 for communications polling and is continuously lit when the HCP-WM(SCI) is operated – in these two states the LED will show red.

The LED will show amber when a short-circuit is present but will switch to red if the unit is activated. The unit operates by pressing the EN54 compliant non-frangible (plastic) element and produces a high level ESP interrupt. A built in

test function initiated by the control panel ensures the integrity of the device at all times and the device can be tested by insertion of a test key in the underside of the unit. Two terminal blocks are provided for easy connection to the loop wiring.

The unit is addressed using the TCH-B100 Hand Held Programmer for quick and reliable addressing. An optional glass element is also available.

**IMPORTANT NOTE:** After changing the element from Glass to Flexi, please confirm the operation by pressing the resettable element.



### Specification

Ingress protection rating	IP67
Colour / case material	Red / Modified Polyphenylene Oxide
Operating voltage	17-41VDC
Low power mode	180 $\mu$ A (max), 100 $\mu$ A (typ)
Quiescent current	350 $\mu$ A (max), 250 $\mu$ A (typ)
Alarm current	10.0 mA (max), 5 mA (typ)
Resistance in positive	100 m $\Omega$ when closed (max), 100 k $\Omega$ when open (min)
Short circuit threshold (typ.)	430 $\Omega$
Transmission method	Digital Communication Using ESP
Operating temperature range	-10°C to +50°C
Storage temperature range	-30°C to +60°C
Max humidity	95%RH Non-condensing (at 40°C)
Weight (g) / Dimensions (mm)	234 / W 98 x H 94 x D 78

\*1 Fire alarm control panel compatibility required for these products.